

Specifications

2010 **4RUNNER**



	SR5 4X2 4-Cyl. 4-Speed Auto	4x2 SR5 V6 5- Speed Auto	4x4 SR5 V6 5- Speed Auto	Trail Edition V6 4x4 5-Speed Auto	4x2 Limited V6 5- Speed Auto	4x4 Limited V6 5- Speed Auto
MECHANICAL						
Engine	2.7-liter DOHC 16-valve EFI VVT-i 4-cylinder 157 hp @ 5200 rpm/178 lb.-ft. @ 3800 rpm		4.0-liter DOHC 24-valve EFI dual independent VVT-i V6 270 hp @ 5600 rpm/278 lb.-ft. @ 4400 rpm			
Emission rating	LEV-II					
Ignition	Electronic, with Toyota Direct Ignition (TDI)					
Transmission	4-speed Electronically Controlled automatic Transmission with intelligence (ECT-i)		5-speed Electronically Controlled automatic Transmission with intelligence (ECT-i) and sequential shift mode			
Body Construction	Reinforced body-on-frame construction					
Suspension	Coil-spring independent double-wishbone front suspension with stabilizer bar; coil-spring independent 4-link with lateral rod rear suspension with stabilizer bar					
Steering	Engine speed-sensing Variable Flow Control (VFC) power-assisted rack-and-pinion					
Turning circle diameter, curb to curb (ft.)	37.4					
Brakes	Power-assisted 4-wheel ventilated disc brakes with 4-wheel Anti-lock Brake System (ABS) (Multi-Terrain ABS on 4Runner Trail), Electronic Brake-force Distribution (EBD) and Brake Assist [23]					
EXTERIOR DIMENSIONS (in.)						
Overall height, unloaded	71.5		74.2		71.5	
Overall width	75.8					
Overall length	189.9					
Wheelbase	109.8					
Track (front/rear)	63.2/63.2					
INTERIOR DIMENSIONS front/second/rear (in.)						
Headroom	39.3/38.6/34.3			N/A		
Headroom with moonroof	38.6/38.6/34.3			38.6/38.6/NA		38.6/38.6/34.3
Shoulder room	57.8/57.8/57.7			57.8/57.8/NA		57.8/57.8/57.7
Hip room	56.5/55.7/43.3			56.5/55.7/NA		56.5/55.7/43.3

Specifications

2010 **4RUNNER**



	SR5 4X2 4-Cyl. 4-Speed Auto	4x2 SR5 V6 5- Speed Auto	4x4 SR5 V6 5- Speed Auto	Trail Edition V6 4x4 5-Speed Auto	4x2 Limited V6 5- Speed Auto	4x4 Limited V6 5- Speed Auto
Leg room	41.7/32.9/29.3			41.7/32.9/NA	41.7/32.9/29.3	
Seating capacity (standard/with optional third-row seat)	5	5/7		5	5/7	
OFF-HIGHWAY						
Approach/departure angle (degrees)	24/24		25/24	33/26	24/24	25/24
Ground clearance (in.)	9.0		9.6		9.0	9.6
WEIGHTS AND CAPACITIES						
Curb weight (lb.)	4295	4400	4675	4750	4525	4805
Gross Vehicle Weight Rating (GVWR) (lb.)	5900	6100		6300		
Towing capacity [5] [29] (lb.)	2000	5000				
Cargo volume [30] (cu. ft.) behind front/rear seats	89.7/47.2			N/A		
Cargo volume [30] (cu. ft.) behind front/rear seats (with sliding deck)	88.8/46.3					
Cargo volume [30] (cu. ft.) behind front/second-row/rear seats	88.8/46.3/9.0			N/A	88.8/46.3/9.0	
Fuel tank (gal.)	24					
TIRES						
Size - Standard	P265/70 R17		P265/60 R20	P265/70 R17	P245/60 R20	
Type	Mud-and-Snow					
Spare	Full-size, mounted under body					
MILEAGE ESTIMATES (city/highway/combined)						
Miles Per Gallon [31]	18/23/20	17/23/19	17/22/19		17/23/19	17/22/19